

NEW HOME CONSTRUCTION BUILDING PERMIT APPLICATION

CITY OF SARTELL
 125 Pinecone Road North
 Sartell, MN 56377-0140
 (320) 258-7317 • Fax (320) 253-3337

FEES

Permit Valuation: _____
 Permit Fee _____
 Plan Check Fee: _____
 Land Dist. Fee: _____
 State Surcharge: _____
 Wac Fee: _____
 Sac Fee: _____
 Sac Surcharge: _____
 Contractor's Lic: _____
 Park Dedication Fee (MF) _____
 Hvac: _____
 Plumbing: _____
 Water Meter: _____
 Penalty: _____
Total Fee: _____
 Fee Pd. Check # _____

 Occupancy Type: _____
 Sprinkled Building: _____

Permit # _____ Today's Date: _____
 Owner of Property: _____
 Site Address: _____
 Phone/email: _____
 Plat: _____ Lot _____ Block _____
 Tax Parcel Number: _____
 County: Stearns _____ Benton _____
 Estimated Construction Valuation: _____

Foundation Type: Full Basement _____ Slab on Grade _____ Crawl Space _____
Lot Size: Front: _____ Rear _____ Side 1 _____ Side 2 _____
Building Structure Setbacks: Front: _____ Rear: _____ Side 1 _____ Side 2 _____
Description: Height: _____ Depth: _____ Width: _____ #Stories: _____
 # Bedrooms _____ # Baths: _____ Proposed Finished Levels: _____
 Notes: _____

Mechanical Code Worksheet Provided _____ **Plumbing Worksheet Provided** _____
Land Disturbance Information:

_____ Storm Water Pollution Prevention Plan (attach copy)
 _____ Best Management Practices proposed on the site (diagram)

Architect/Engineer/Designer _____ Phone: _____
 Builder _____ License # _____ Phone: _____
 Electrician: _____ Phone: _____
 HVAC: _____ State Bond # _____ Phone: _____
 Plumber: _____ State Lic # _____ Bond # _____ Phone: _____
 Water/Sewer Installer: _____ Phone: _____
 Fire Suppression: _____ Phone: _____

 Applicant Name (Print) Phone #

 Building Inspector

 Applicant Signature

 City Clerk

 Company

The undersigned agrees that by signing of this application obligates the Applicant to adhere to any and all ordinances and regulations adopted by the City of Sartell, as well as requests for further protection as deemed necessary by any employee or agent of the City of Sartell, Stearns or Benton County, or State of Minnesota. Failure to comply with the approved site or building plans may result in a Stop Work Order. Compliance with the standards of the Sartell's Environmental Ordinance will not guarantee satisfaction of the requirements of the MPCA. I further grant the right-of-entry onto this property, as described above, to the designated personnel of the City of Sartell for the purpose of inspecting and monitoring for compliance with the provisions of this permit and Sartell Code Chapter 20.

*NOTE: For the construction of new buildings, the applicant is responsible for establishing the final grade as designed and approved through the site plan and/or plat approval to maintain positive drainage away from the building foundation. The Applicant acknowledges that all of the information or statements provided on this application are true and all work will be done in accordance with the Ordinances of the City of Sartell, the Minnesota State Building Code and the Building Inspection Department.



**CITY OF SARTELL
SUBMITTAL CHECK LIST & QUESTIONNAIRE FOR NEW HOMES
2015 STATE BUILDING CODE**

The City of Sartell must receive the following information to start reviewing your application. Your building permit application will not be accepted until ALL of the items are received and the questions are answered.

_____ Building Permit Application (must include land disturbance information, plumbing and mechanical contractor information, which includes state bond and license information).

_____ Two sets of plans (1 copy of plan drawn to 1/8 or 1/4 inch scale and 1 copy on 11x17 paper).

_____ Two copies of site plan or survey verifying all items listed below.

- Plat of lot
- Lot/Block designation
- Easements-dimensioned and drawn to scale
- Pin number and tax I.D. number
- Building setbacks (all sides) to property lines and adjacent structures
- House, garage and driveway must be identified with elevations & dimensions to corners
- Drainage information (spot elevations, grading slopes (H:V), drainage arrows)
- Sediment and Erosion Control measures (Silt fence, bio rolls, etc.)
- Location of rock entrance (6 inch depth and required length up to 50ft)

_____ One copy of 2015 Energy Code Worksheet (MN. Rules Chapter 1322/2012 IECC).

_____ One copy of the 2015 Mechanical Code Worksheet (combustion air and make-up air worksheets if applicable).

_____ One copy of the 2015 Plumbing Code Worksheet

_____ One copy of the 2015 Additional Features Check List.

Please answer the following questions. In a development where a grading plan has been completed, the curb elevation must be the actual elevation taken at the site and based on benchmark elevations from the development's approved grading plan.

Bench Mark Location: _____ Bench Mark Elevation: _____

Top of curb elevation (at approach & must be obtained at the site): _____

Garage Floor: _____ Driveway Slope (%): _____

Main Floor: _____ Top of Foundation: _____

Low Floor: _____ Top of Footing: _____

Lowest opening: _____ Walk-out: (Y / N) Lookout: (Y / N)

I hereby certify that I have read and examined this submittal checklist and questionnaire and know the same to be true and correct

Name (print) _____ Signature _____ Date _____

Once all of the items have been submitted and questions answered, the completed submittal documents can be delivered to Sartell City Hall located at 125 Pinecone Road North. **Do not send any checks or money with the application and submittal documents.** Upon completion and approval of the plans and specifications by the City of Sartell the applicant will be notified that the permit is ready to be picked up and paid for. No work can be commenced or inspections scheduled until the permit has been approved and obtained from the City. **A SITE INSPECTION IS REQUIRED BEFORE ANY EXCAVATION WORK BEGINS.** Completed applications will expire if they are not picked up at the City within 180 days from the approval date (MN. Rules 1300.0120 subp. 9)

.....



**CITY OF SARTELL
 NEW SINGLE FAMILY DWELLING - 2015 STATE BUILDING CODE
 ADDITIONAL FEATURES CHECK LIST
 Must be completed by the Building Permit Applicant**

Site Address _____

PLEASE CHECK ALL THE ITEMS THAT APPLY TO YOUR PROJECT

_____ Passive Radon System being provided

_____ Active Radon System being provided

_____ The building or portion of the building will be used for a licensed child care, adult care, supervised living, hospice, foster care, senior housing, boarding care, housing with services, boarding and lodging, congregate residence or other type licensed facility. Lic. type _____

_____ Automatic fire sprinkler system provided.

System type: Stand-alone _____ multi-purpose (pex system) _____

_____ Finished lower level(s) (Plans must indicate which areas are to be finished).

_____ Exterior deck to be provided (plans must be provided). A completed copy of the Deck Ledger Attachment Worksheet must be provided if the deck is **not** self-supporting.

_____ Three season or screen porch (plans must be provided). A completed copy of the Deck Ledger Attachment Worksheet must be provided if the deck is **not** self-supporting.

_____ In-Floor heat (Wirsbo)

_____ Garage will be heated

_____ Wood foundation

_____ I.C.F. foundation: Manufactured specs provided _____ IRC _____

_____ Poured wall foundation _____ Integral Type: Engineered _____ IRC _____ ACI _____

*Engineered and ACI design specs must be provided with application

Height of foundation wall _____ Wall thickness _____

_____ Masonry foundation _____ Type: Engineered _____ IRC _____ ACI _____

*Engineered and ACI design specs must be provided with application

Height of foundation wall _____ Block width _____

_____ Geo-Thermal System: Well Type: Vertical| _____ Horizontal _____

_____ Solar Powered Systems

_____ Curb cut needed

_____ Lawn Irrigation System (lawn irrigation permit required) _____ Back flow preventer needed

Name (print)

Signature

Date

DECK LEDGER ATTACHMENT WORKSHEET

This worksheet is not required for self-supporting decks.

Deck ledgers attached to the home which support the floor live load must comply with the connection requirements in IRC R507 and must be visible inside the home or the deck must be designed to be self-supporting. Are the rims exposed where deck is attached Yes ____ No ____

IRC R507:

1. Existing Dwelling Floor System Type:

- Trusses: O.C. spacing _____ Depth _____ Rim material and thickness _____
- I Joist: O.C. spacing _____ Size _____ Rim material and thickness _____
- Dimension Lumber: O.C. spacing _____ Size _____ Grade _____ Species _____

2. Ledger Board:

- Size _____ Grade _____ Species _____

3. Ledger Board Fasteners:

- Type _____
- Length _____
- Placement _____

4. Lateral Load Connection:

- Type of Connector _____
- Manufacturer _____
- Model/Part# _____

ENGINEERED CONNECTION:

1. Name of Licensed Design Professional providing the designed connection:

2. Is a copy of the construction details drawn by the Design Professional included with the submittal of plans?

Yes _____ No _____

Signature: _____ Date: _____

Print Name: _____



2015 PLUMBING CODE WORKSHEET FOR NEW HOMES

THIS WORKSHEET MUST BE COMPLETED BY THE PLUMBING CONTRACTOR AND/OR LICENSED BUILDER

FIXTURES (provide numbers of each type being provided or installed):

Floor Drains (include garage) _____

Water Closets (toilets) _____

Lavatories _____

Bathtubs _____

Showers _____

Kitchen Sinks _____

Bar Sinks _____

Laundry Tub/Sink _____

Clothes Washer Drains _____

Sump Pump and Discharge Pipe _____

Water Conditioner (softener) _____

Water Heater(s) _____

Sewage Ejector _____

Other (describe) _____

WATER HEATER:

Electric _____ Gas _____ Other (describe) _____

Tank Size (gal.) _____

Venting Type: Power Vent _____ Direct Vent _____

BTU _____

BOILER:

Electric: Size _____

Gas: BTU _____ Efficiency Rating _____ Direct Vented _____ Power Vented _____

BACKFLOW PREVENTOR:

PVB (lawn irrigation) _____

Double Check Valve with Intermediate Atmospheric Vent (boiler) _____

Double Check Valve (Fire Sprinkler) _____

RPZ _____

Other _____

Address of new home project: _____



2015 MECHANICAL CODE WORKSHEET FOR NEW HOMES

THIS WORKSHEET MUST BE COMPLETED BY THE MECHANICAL CONTRACTOR OR LICENSED BUILDER

This worksheet and applicable make-up air and/or combustion air worksheets must be Completed and provided with the permit application. Provide information on all applicable items.

GAS PIPING:

TYPE INSTALLED: _____

FURNACE 1:

BTU _____ EFF. RATING _____ DIRECT VENTED _____ POWER VENTED _____

FURNACE 2:

BTU _____ EFF. RATING _____ DIRECT VENTED _____ POWER VENTED _____

AIR HANDLER:

MANUFACTURER _____ MODEL# _____

BOILER:

ELECTRIC: SIZE _____

GAS: BTU _____ EFF. RATING _____ DIRECT VENTED _____ POWER VENTED _____

FIREPLACE:

WOOD: MANUFACTURER _____ MODEL# _____ VENTING TYPE _____

GAS 1: SIZE _____ DIRECT VENTED _____ POWER VENTED _____

GAS 2: SIZE _____ DIRECT VENTED _____ POWER VENTED _____

GARAGE HEATER:

ELECTRIC: SIZE _____

GAS: SIZE _____ DIRECT VENTED _____ POWER VENTED _____

VENTILATION SYSTEM (balanced system required):

HRV: MANUFACTURER _____ MODEL# _____ TOTAL CFM _____ CONT. _____

ERV: MANUFACTURER _____ MODEL# _____ TOTAL CFM _____ CONT. _____

Circle one

VENT. FAN: MANUF. _____ MODEL# _____ LOCATION _____ CFM _____ intake/ex.

VENT. FAN: MANUF. _____ MODEL# _____ LOCATION _____ CFM _____ intake/ex.

EXHAUST FANS:

BATH/UTILITY FAN: LOCATION _____ CFM _____

BATH/UTILITY FAN: LOCATION _____ CFM _____

BATH/UTILITY FAN: LOCATION _____ CFM _____

OTHER: LOCATION _____ CFM _____

RANGE HOOD:

MANUFACTURER _____ MODEL# _____ CFM _____

MAKE-UP AIR: Make-up air must be sized in accordance with the state mechanical code CH 1346, worksheet 501.4.1 and Table 501.4.2 A completed copy of worksheet 501.4.1 must be provided.

PASSIVE _____ LOCATION _____ SIZE _____

POWERED _____ MANUF. _____ MODEL# _____ LOCATION _____ CFM _____

COMBUSTION AIR: Worksheet E-1 must be provided if combustion appliances (including water heater) are atmospheric or fan assist/power vented type (NA for electric or direct vented appliances).

Combustion air ducts must be sized in accordance with the 2015 state mechanical code CH 1346 Appendix E, Worksheet E-1 (attached) and a copy must be provided.

SIZE (dia.) _____ METAL _____ FLEX _____

EQUIPMENT SIZING: Heating Loss _____ Heating Gain _____ Cooling Load _____

_____ Heating and cooling equipment was sized in accordance with ACCA manual S based on building loads calculated in accordance with ACCA manual J and a copy is attached.

_____ Heating and cooling equipment was sized by other approved and accepted methods. Describe:

I acknowledge that to the best of my ability all of the information or statements provided is true and accurate.

Date _____ Name (print) _____ Signature _____

Company _____

Address of new home project: _____

1346.6012 IFGC APPENDIX E, WORKSHEET E-1.

IFGC Appendix E, Worksheet E-1 Residential Combustion Air Calculation Method (for Furnace, Boiler, and/or Water Heater in the Same Space)	
Step 1:	Complete vented combustion appliance information: Furnace/Boiler: ___ Draft Hood ___ Fan Assisted ___ Direct Vent Input: ___ Btu/hr (Not fan Assisted) & Power Vent Water Heater: ___ Draft Hood ___ Fan Assisted ___ Direct Vent Input: ___ Btu/hr (Not fan Assisted) & Power Vent
Step 2:	Calculate the volume of the Combustion Appliance Space (CAS) containing combustion appliances. The CAS includes all spaces connected to one another by code compliant openings. CAS volume: ___ ft ³
Step 3:	Determine air Changes per Hour (ACH) ¹ Default ACH values have been incorporated into Table E-1 for use with Method 4b (KAIR Method). If the year of construction or ACH is not known, use method 4a (Standard Method).
Step 4:	Determine Required Volume for Combustion Air. 4a. Standard Method Total Btu/hr input of all combustion appliances (DO NOT COUNT DIRECT VENT APPLIANCES) Input: ___ Btu/hr Use Standard Method column in Table E-1 to find Total Required Volume (TRV) TRV: ___ ft ³ If CAS Volume (from Step 2) is greater than TRV then no outdoor openings are needed. If CAS Volume (from Step 2) is less than TRV then go to STEP 5 . 4b. Known Air Infiltration Rate (KAIR) Method Total Btu/hr input of all fan-assisted and power vent appliances (DO NOT COUNT DIRECT VENT APPLIANCES) Input: ___ Btu/hr Use Fan-Assisted Appliances column in Table E-1 to find Required Volume Fan Assisted (RVFA) RVFA: ___ ft ³ Total Btu/hr input of all non-fan-assisted appliances Input: ___ Btu/hr Use Non-Fan-Assisted Appliances column in Table E-1 to find Required Volume Non-Fan-Assisted (RVNFA) RVNFA: ___ ft ³ Total Required Volume (TRV) = RVFA + RVNFA TRV = ___ + ___ = ___ ft ³ If CAS Volume (from Step 2) is greater than TRV then no outdoor openings are needed. If CAS Volume (from Step 2) is less than TRV then go to STEP 5 .
Step 5:	Calculate the ratio of available interior volume to the total required volume. Ratio = CAS Volume (from Step 2) divided by TRV (from Step 4a or Step 4b) Ratio = ___ / ___ = ___
Step 6:	Calculate Reduction Factor (RF). RF = 1 minus Ratio RF = 1 - ___ = ___
Step 7:	Calculate single outdoor opening as if all combustion air is from outside. Total Btu/hr input of all Combustion Appliances in the same CAS (EXCEPT DIRECT VENT) Input: ___ Btu/hr Combustion Air Opening Area (CAOA): Total Btu/hr divided by 3000 Btu/hr per in ² CAO A = ___ /3000 Btu/hr per in ² = ___ in ²
Step 8:	Calculate Minimum CAO A. Minimum CAO A = CAO A multiplied by RF Minimum CAO A = ___ x ___ = ___ in ²
Step 9:	Calculate Combustion Air Opening Diameter (CAOD) CAOD = 1.13 multiplied by the square root of Minimum CAO A CAOD = 1.13 x √Minimum CAO A = ___ in

¹If desired, ACH can be determined using ASHRAE calculation or blower door test. Follow procedures in Section 304.

1346.6014 IFGC APPENDIX E, TABLE E-1.

IFGC Appendix E, Table E-1					
Residential Combustion Air Required Volume (Required Interior Volume Based on Input Rating of Appliances)					
Input Rating (Btu/hr)	Standard Method (ft ³)	Known Air Infiltration Rate (KAIR) Method (ft ³)			
		Fan Assisted		Non-Fan-Assisted	
		1994 ¹ to Present	Pre 1994 ²	1994 ¹ to Present	Pre 1994 ²
5,000	250	375	188	525	263
10,000	500	750	375	1,050	525
15,000	750	1,125	563	1,575	788
20,000	1,000	1,500	750	2,100	1,050
25,000	1,250	1,875	938	2,625	1,313
30,000	1,500	2,250	1,125	3,150	1,575
35,000	1,750	2,625	1,313	3,675	1,838
40,000	2,000	3,000	1,500	4,200	2,100
45,000	2,250	3,375	1,688	4,725	2,363
50,000	2,500	3,750	1,875	5,250	2,625
55,000	2,750	4,125	2,063	5,775	2,888
60,000	3,000	4,500	2,250	6,300	3,150
65,000	3,250	4,875	2,438	6,825	3,413
70,000	3,500	5,250	2,625	7,350	3,675
75,000	3,750	5,625	2,813	7,875	3,938
80,000	4,000	6,000	3,000	8,400	4,200
85,000	4,250	6,375	3,188	8,925	4,463
90,000	4,500	6,750	3,375	9,450	4,725
95,000	4,750	7,125	3,563	9,975	4,988
100,000	5,000	7,500	3,750	10,500	5,250
105,000	5,250	7,875	3,938	11,025	5,513
110,000	5,500	8,250	4,125	11,550	5,775
115,000	5,750	8,625	4,313	12,075	6,038
120,000	6,000	9,000	4,500	12,600	6,300
125,000	6,250	9,375	4,688	13,125	6,563
130,000	6,500	9,750	4,875	13,650	6,825
135,000	6,750	10,125	5,063	14,175	7,088
140,000	7,000	10,500	5,250	14,700	7,350
145,000	7,250	10,875	5,438	15,225	7,613
150,000	7,500	11,250	5,625	15,750	7,875
155,000	7,750	11,625	5,813	16,275	8,138
160,000	8,000	12,000	6,000	16,800	8,400
165,000	8,250	12,375	6,188	17,325	8,663
170,000	8,500	12,750	6,375	17,850	8,925
175,000	8,750	13,125	6,563	18,375	9,188
180,000	9,000	13,500	6,750	18,900	9,450
185,000	9,250	13,875	6,938	19,425	9,713
190,000	9,500	14,250	7,125	19,950	9,975
195,000	9,750	14,625	7,313	20,475	10,238
200,000	10,000	15,000	7,500	21,000	10,500
205,000	10,250	15,375	7,688	21,525	10,763
210,000	10,500	15,750	7,875	22,050	11,025
215,000	10,750	16,125	8,063	22,575	11,288
220,000	11,000	16,500	8,250	23,100	11,550
225,000	11,250	16,857	8,438	23,625	11,813
230,000	11,500	17,250	8,625	24,150	12,075

¹The 1994 date refers to dwellings constructed under the 1994 Minnesota Energy Code. The default KAIR used in this section of the table is 0.20 ACH.

²This section of the table is to be used for dwellings constructed prior to 1994. The default KAIR used in this section of the table is 0.40 ACH.

Table 501.4.1
Procedure to Determine Makeup Air Quantity for Exhaust Equipment in Dwellings
 Use the Appropriate Column to Estimate House Infiltration

	One or multiple power vent or direct vent appliances or no combustion appliances ^A	One or multiple fan-assisted appliances and power vent or direct vent appliances ^B	One atmospherically vented gas or oil appliance or one solid fuel appliance ^C	Multiple atmospherically vented gas or oil appliances or solid fuel appliances ^D
1 a) pressure factor (cfm/sf)	0.15	0.09	0.06	0.03
b) conditioned floor area (sf) (including unfinished basements)				
Estimated House Infiltration (cfm): [1a x 1b]				
2. Exhaust Capacity				
a) continuous exhaust-only ventilation systems (cfm): (not applicable to balanced ventilation systems such as HRV)				
b) clothes dryer	135	135	135	135
c) 80% of largest exhaust rating (cfm): (not applicable if recirculating system or if powered makeup air is electrically interlocked and matched to exhaust)				
d) 80% of next largest exhaust rating (cfm): (not applicable if recirculating system or if powered makeup air is electrically interlocked and matched to exhaust)	not applicable			
Total Exhaust Capacity (cfm): [2a+2b+2c+2d]				
3. Makeup Air Requirement				
a) Total Exhaust Capacity (from above)				
b) Estimated House Infiltration (from above)				
Makeup Air Quantity (cfm): [3a - 3b] (if value is negative, no makeup air is needed)				
4. For Makeup Air Opening Sizing, refer to Table 501.3.2				

- ^A Use this column if there are other than fan-assisted or atmospherically vented gas or oil appliances or if there are no combustion appliances.
- ^B Use this column if there is one fan-assisted appliance per venting system. Other than atmospherically vented appliances may also be included.
- ^C Use this column if there is one atmospherically vented (other than fan-assisted) gas or oil appliance per venting system or one solid fuel appliance.
- ^D Use this column if there are multiple atmospherically vented gas or oil appliances using a common vent or if there are atmospherically vented gas or oil appliances and solid fuel appliances.

**Table 501.4.2
Makeup Air Opening Sizing Table for New and Existing Dwellings**

	One or multiple power vent or direct vent appliances or no combustion appliances ^A	One or multiple fan-assisted appliances and power vent or direct vent appliances ^B	One atmospherically vented gas or oil appliance or one solid fuel appliance ^C	Multiple atmospherically vented gas or oil appliances or solid fuel appliances ^D	Passive makeup air opening duct diameter ^{E,F,G}
Type of opening or system	(cfm)	(cfm)	(cfm)	(cfm)	(inches)
Passive Opening	1-36	1-22	1-15	1-9	3
Passive Opening	37-66	23-41	16-28	10-17	4
Passive Opening	67-109	42-66	29-46	18-28	5
Passive Opening	110-163	67-100	47-69	29-42	6
Passive Opening	164-232	101-143	70-99	43-61	7
Passive Opening	233-317	144-195	100-135	62-83	8
Passive Opening with Motorized Damper	318-419	196-258	136-179	84-110	9
Passive Opening with Motorized Damper	420-539	259-332	180-230	111-142	10
Passive Opening with Motorized Damper	540-679	333-419	231-290	143-179	11
Powered Makeup Air ^H	>679	>419	>290	>179	not applicable

^A Use this column if there are other than fan-assisted or atmospherically vented gas or oil appliances or if there are no combustion appliances.

^B Use this column if there is one fan-assisted appliance per venting system. Other than atmospherically vented appliances may also be included.

^C Use this column if there is one atmospherically vented (other than fan-assisted) gas or oil appliance per venting system or one solid fuel appliance.

^D Use this column if there are multiple atmospherically vented gas or oil appliances using a common vent or if there are atmospherically vented gas or oil appliances and solid fuel appliance(s).

^E An equivalent length of 100 feet of round smooth metal duct is assumed. Subtract 40 feet for the exterior hood and ten feet for each 90-degree elbow to determine the remaining length of straight duct allowable.

^F If flexible duct is used, increase the duct diameter by one inch. Flexible duct shall be stretched with minimal sags.

^G Barometric dampers are prohibited in passive makeup air openings when any atmospherically vented appliance is installed.

^H Powered makeup air shall be electrically interlocked with the largest exhaust system.



THIS WORKSHEET MUST BE COMPLETED BY THE BUILDING PERMIT APPLICANT

2015 MN Residential Energy Code (MN Rules 1322 and 2012 IECC)
Prescriptive compliance building envelope information Sheet for new home construction

*BUILDING ENVELOPE

Above Grade:

Table with 3 columns: Insulation being installed, Type, R-Value. Rows include Roof/Ceiling, Wood Framed Walls, Mass Walls, Rim(s), and Floor/Ceiling(s).

Below Grade (walls greater than or equal to 50% below grade):

I am using the exception in 1322.402.2.8 and intend to install foundation insulation only on the exterior side of the foundation wall, the home's tested air leakage rate (blower door test) will not exceed 2.6 air changes per hour and the top of foundation wall does not exceed 1.5 times the total lineal feet of each foundation wall enclosing conditioned space.

A. Bsmt/Crawl Space Walls

Exterior Draining Foundation Insulation
Exterior Non-draining Foundation Insulation

- Exterior
Interior

B. Slab-On-Grade/Frost Walls

- Exterior
Interior

Table with 2 columns: Fenestration, U-Factor. Rows include Windows, Doors, and Skylight.

*If the attached garage is intended to be conditioned, the building envelope for the garage must comply with the building envelope requirements same as the dwelling.

ADDITIONAL REQUIREMENTS

Building Envelope

- 1. Foundation waterproofing must extend from the top interior wall edge, across the top of the wall, and down the exterior wall face to the top of footing.



2. Foundation insulation applied to the exterior foundation walls shall have a weather-resistant protective covering to prevent the degradation of the insulation's thermal performance. Such covering must extend a minimum of 6 inches below grade.
3. Exterior non-draining foundation insulation must be covered with a 6-mil polyethylene slip sheet over the entire exterior surface.
4. Windows, skylights and sliding glass doors shall have an air infiltration rate not exceeding 0.3 CFM per square foot and swinging doors no more than 0.5.
5. A continuous sealed air barrier must be provided in the building envelope, including the separation wall/ceiling between the attached garage and house. Exterior thermal envelope must contain a continuous air barrier.
6. The interior air barrier in any dropped ceiling/soffit shall be aligned with the insulation.
7. Access openings to attics and other unconditioned spaces shall be weather-stripped and insulated.
8. Attic insulation markers shall be provided at least one in every 300 square feet throughout the attic space and shall face the attic access opening.
9. Headers shall be insulated.
10. The connection of sill plate and foundation shall be sealed.
11. Rim joist insulation must include the air barrier.
12. The air barrier must be provided on exterior walls between tubs/showers and within fireplace enclosures.
13. Electrical or communication boxes which penetrate the air barrier must be air sealed boxes.
14. The insulation installer shall provide a certificate listing the type, manufacturer, initial installed thickness, settled thickness, settled R-Value, installed density, coverage area and number of bags for blown in fiberglass or cellulose insulation. For sprayed polyurethane foam, the installed thickness, area covered and R-Value of installed thickness shall be provided on the certificate.
15. The building shall be tested (Blower Door) and verified as having an air leakage rate not exceeding 3 air changes per hour in accordance with IECC R402.4.1.2. A copy of the report shall be signed by the approved party conducting the test and provided to the Code Official.
16. A compliance certificate shall be completed by the builder or design professional, provided to the inspector on final inspection and posted on or in the electrical panel box.

Plumbing/Mechanical

1. Provide documentation showing that heating and cooling equipment was sized in accordance with ACCA Manual S based on building loads calculated in accordance with ACCA Manual J.
2. All ducts located outside the building thermal envelope shall be independently insulated to a minimum R-8 and provided with a vapor barrier. Air intake and exhaust ducts within the building envelope must be insulated with R-3.3 and provided with a vapor barrier for a minimum distance of 3 feet from the exterior or unconditioned space. See MN Rules 1322.0403 for additional information and requirements.
3. Outdoor air intakes and exhausts shall have automatic or gravity dampers that close when the ventilation system is not operating.
4. Building framing cavities shall not be used as ducts or plenums.
5. All ducts, air handlers and filter boxes must be sealed with listed and labeled tapes, gaskets, mastics or other approved systems and materials in accordance with MN Rules 1346.603.9.



6. A duct leakage test is required in accordance with IECC R403.2.2 when all ducts or air handlers are not located entirely within the building envelope.
7. Air handlers shall have a manufacturer's designation for an air leakage of no more than 2 percent of the design air flow rate in accordance with ASHRAE 193.
8. Forced air furnaces must be equipped with a programmable thermostat capable of controlling the heating and cooling on a daily schedule to maintain different temperature set points at different times of the day.
9. Heat pumps must be equipped with a two-stage thermostat that controls the back-up heat on its second stage.
10. Mechanical systems piping carrying fluids above 105 deg F or below 55 deg F shall be insulated to a minimum of R-3.
11. The following domestic hot water piping shall be insulated to a minimum of R-3.
 - From the water heater to the kitchen outlets.
 - Outside the conditioned space.
 - From water heater to distribution manifold.
 - Under a slab.
 - Buried piping.
 - Supply and return piping on recirculation systems.
 - 3/8 inch piping with a run length greater than 30 feet
 - 1/2 inch piping with a run length greater than 20 feet.
 - 3/4 inch piping with a run length greater than 10 feet.
 - Piping greater than 3/4 inch with a run length exceeding 5 feet.
12. Circulating hot water systems shall be provided with an automatic or readily accessible manual switch that can turn off the hot-water circulation pump when the system is not in use.

Electrical

1. A minimum of 75% of the lamps in permanently installed lighting fixtures shall be high-efficiency lamps.
2. Recessed luminaries installed in the building thermal envelope shall be sealed to limit air leakage and shall be IC-rated and labeled as having an air leakage rate not more than 2.0 CFM as tested in accordance with ASTM E 283. A gasket or approved sealant shall be provided between the housing and interior wall or ceiling covering.

All materials, systems and equipment shall be installed in accordance with the manufacturer's installation instructions and the 2015 State Building Code.

I acknowledge that to the best of my ability, all of the information or statements I have provided is true and accurate and that I have read and understand all of the above information provided.

Date _____ Name (Print) _____ Signature _____



MEMO

DATE: January 30, 2015
TO: Building, Mechanical and Plumbing Contractors
FROM: Jill Hollenkamp, Permit Technician
SUBJECT: **Permits & Inspections**

If you would like to have a copy of your issued permits and Inspection Notices emailed to you please provide your email on the space provided on the application and I will email your copy of the issued permit and all you're Inspection Notices.

Please remember as the contractor it is your responsibility to make sure that the required inspections are completed. This includes final inspections on furnace change outs, water heaters and water softeners, etc. Leaving the Inspection Card and expecting the homeowner to know to call for an inspection does not always work and often times does not happen.

Please call my direct line to schedule ALL of your inspections (building, plumbing and mechanical) and for any questions you might have about permits. If I am not available when you call please leave me a message and I will call you back to schedule your inspection. My direct line is **320-258-7317** or email jill@sartellmn.com

**City of Sartell
Contact & Other Helpful Information**

Kyle Christensen, Chief Building Official: 320-258-7308 kyle@sartellmn.com

Butch Rieland, Fire Marshal/Code Official: 320-258-7307 butch@sartellmn.com

Jill Hollenkamp, Permit Technician: 320-258-7317 jill@sartellmn.com

Darrel Nemeth, Electrical Inspector: 320-654-6634 (call for all electrical inspections)

- Inspection Records (yellow card) and Inspection Record Notices must be maintained/posted at a visible and accessible location on the project. Inspections may not be performed if card, inspection slips and plans are not available to inspector. This could result in a re-inspection fee.